

■ EPL3000-10KTL



Big LCD display



Power export limit



Compact and easy to install



Wifi / GPRS / Lan communication optional



Great reliability



Good safety and quality



Specifications

Model	EPL3000TL	EPL4000TL	EPL5000TL	EPL6000TL	EPL8000TL	EPL10KTL
Input(DC)						
Max DC power	4500W	6000W	7500W	9000W	12000W	14000W
Max DC voltage	500 V					
MPPT voltage range	100~450 Vd.c.					
Rated PV Input Voltage	360V (100-500V)					
Full Load DC Voltage Range	200-425V					
PV Input Current	13+13A				26+26A	
Max.PV Isc	25+25				50+50	
Number of MPPT trackers			2			
Number of input string	1+1				2+1	
Battery Input						
Battery Type	Lead-acid or Li-ion					
Battery voltage range	40-60V					
Maximum charge current	80A	100A	120A	150A	200A	210A
Maximum discharge current	80A	100A	120A	150A	200A	210A
External Temperature Sensor	Yes					
Charging Curve	3 Stages/Equalization					
Charging Strategy for Li-Ion Batteries	Self-adaption to BMS					
Output (AC)						
Rated AC Output Active Power	3000W	4000W	5000W	6000W	8000W	10000W
Maximum AC Output Active Power	3300W	4400W	5500W	6600W	8800W	10500W
AC Output Rated Current	13.1A	17.4A	21.7A	26.1A	34.8A	43.5A
Maximum AC Output Current	15A	20A	25A	28.8A	38.5A	45.6A
Maximum Continuous AC Passthrough	35A				50A	
Peak Power(off grid)	2 time of rated power, 10s					
Power Factor Adjustment Range	0.8 leading to 0.8 lagging					
Power Factor	1					
Output Frequency and Voltage	50/60HZ; L/N/PE 220/230Vac					
Grid Type	single phase					
Total Harmonic Distortion(THD)	<0.5% In					
Efficiency						
Max efficiency	97.60%				97.80%	
Euro efficiency	95.60%				96.60%	
MPPT efficiency	99.90%					
Protection						
Interrated	Anti-islanding protection, PV String Input Reverse Polarity Protection					
	Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection					
	Output Shorted Protection, Surge Protection					
Over Voltage Category	DC Type II/AC Type III					
General Data						
Operating temperature range	-40~60°C , >45°C Derating					
Cooling	Smart Cooling					
Noise	<=30db					
Communication with BMS	RS485 ; CAN					
Weight	25KG					
Dimension (W/H/D)	520*510*55					
Degree of protection	IP65					
Installation Style	Wall-mounted					
Warranty	5 years (10 Years Optional)					